



















All Supports are available in epoxy coated, galvanized or plain finish.




ITEM	WIRE SIZE		DESCRIPTION
	Top Wire	Legs	
SLAB BOLSTER (SB) 	No. 4	No. 6	<ul style="list-style-type: none"> • Legs spaced 5" at centers - Heights from 3/4" up to 3".
SLAB BOLSTER PLASTIC TIPPED (SBPT) 	No. 4	No. 6	<ul style="list-style-type: none"> • Legs spaced 5" at centers - Heights from 3/4" up to 3". • Available in plastic dipped and epoxy coated plastic dipped from 1" to 3"
SLAB BOLSTER UPPER (SBU) 	No. 4	No. 6	<ul style="list-style-type: none"> • Same as SB with #7 wire runners
SLAB BOLSTER WITH PLATE (SBP) 	No. 4	No. 6	<ul style="list-style-type: none"> • Same as SB with (2) 1" x 20 gauge steel plate
BEAM BOLSTER (BB) 	No. 7 up to 2" No. 4 over 2"		<ul style="list-style-type: none"> • All legs spaced 2.5: centers - maximum height 5".
BEAM BOLSTER PLASTIC TIPPED (BBPT) 	No. 7 up to 2" No. 4 over 2"		<ul style="list-style-type: none"> • All legs spaced 2.5: centers - maximum height 5".

All Supports are available in epoxy coated, galvanized or plain finish.

ITEM	WIRE SIZE		DESCRIPTION
	Top Wire	Legs	
BEAM BOLSTER UPPER (BBU) 	No. 7 up to 2" No. 4 over 2"		<ul style="list-style-type: none"> All legs spaced 2.5: centers - maximum height 5". No. 7 Wire Runners up to 2". No. 4 Wire Runners over 2".
HEAVY BAR CHAIR (HBC) 	No. 4	No. 4	<ul style="list-style-type: none"> Made and stocked only in 3/4", 1", 1.5" and 1.75" heights.
HEAVY BAR CHAIR WITH PLASTIC TIPS (HBCPT) 	No. 4	No. 4	<ul style="list-style-type: none"> Made and stocked only in 3/4", 1", 1.5" and 1.75" heights.
INDIVIDUAL HIGH CHAIR (HC) 	No. 4 from 2" to 5" No. 2 over 5" to 9" No. 0 over 9"		<ul style="list-style-type: none"> Legs at 20" or less with vertical. When height exceeds 12" reinforce legs with welded cross wires or encircling wire.
INDIVIDUAL HIGH CHAIR (HCPT) 	No. 4 from 2" to 5" No. 2 over 5" to 9" No. 0 over 9"		<ul style="list-style-type: none"> Legs at 20" or less with vertical. When height exceeds 12" reinforce legs with welded cross wires or encircling wire.
INDIVIDUAL HIGH LOW CHAIR (HLC) 	No. 4 from 2" to 5" No. 2 over 5" to 9" No. 0 over 9"		 <ul style="list-style-type: none"> Specify Type A or Type B when ordering

All Supports are available in epoxy coated, galvanized or plain finish.

ITEM	WIRE SIZE		DESCRIPTION
	Top Wire	Legs	
INDIVIDUAL HIGH CHAIR WITH PLATE (HCP) 	No. 4 from 2" to 5" No. 2 over 5" to 9" No. 0 over 9"		<ul style="list-style-type: none"> • Same as HC with 20 Gauge Plate/s
CONTINUOUS HIGH CHAIR (CHC) 	No. 2	Same as HC	<ul style="list-style-type: none"> • All legs 8" centers with leg within 4" of end of chair. Also available with plastic tips
CONTINUOUS HIGH CHAIR UPPER (CHCU) 	Same as CHC No. 4 over 2"	Same as HC	<ul style="list-style-type: none"> • Same as CHC with No. 4 wire runners
CONTINUOUS HIGH CHAIR WITH PLATE (CHCP) 	Same as CHC	Same as HC	<ul style="list-style-type: none"> • Same as CHC with 20 gauge plate/s
DOWEL BASKETS (DB) 	TBD - Made to order		<ul style="list-style-type: none"> • Contraction, Transverse, Longitudinal and Tie Bar Baskets are made to each state's DOT specifications. • Please specify dowel diameter and length, spacing, slab thickness and coatings (epoxy, tectyl, red oxide) when requesting a quote

ITEM	OPTIONS	DESCRIPTION
<p>SNAP TIE</p> 	<ul style="list-style-type: none"> • Ends: 4 ¾" (SE) or 8 ¼" (LE) • Wall thickness: 4" minimum and up 	<ul style="list-style-type: none"> • Available in plastic cone (PC), metal cone (MC), and special cone • Standard snap-tie or heavy duty • Waterseal available
<p>COIL TIE</p> 	<ul style="list-style-type: none"> • Diameter: ½", ¾", 1" • Wall thickness: 6" minimum and up 	<ul style="list-style-type: none"> • 2 strut, 4 strut • Screw on, standard • Water seal available
<p>FLAT TIE</p> 	<ul style="list-style-type: none"> • Wall thickness: 4" minimum and up 	<ul style="list-style-type: none"> • "X" flat tie used with steel plywood forming (V-Form)